



ALLBÄCK LINUS WALL PAINT – QUALITY CONTROL FOR HANDLING, USE AND MAINTENANCE

Allbäck Linoljeprodukter AB
Balkåkravägen 18
271 91 Ystad, Sweden

Product name: **Allbäck** Linus Wall Paint
Binder: **Allbäck** cleaned, boiled and matured linseed oil
Thinner: If necessary, water, approx. 10%

Area of use:

Linus Wall Paint contains only purified cleaned boiled linseed oil, water, cellulose glue, shellac, titanium dioxide, and chalk. The pigments are iron oxides and/or chromium oxide depending on the colour. The paint is solvent-free and must never be thinned with solvents.

BUILDING MATERIAL ASSESSMENT – GREEN ARROW. SUNDA HUS – A.

Surface	The paint may be used on all interior surfaces: wood, painted surfaces, plaster, wallpaper, whitewash, plasterboard, woven surfaces, and prepared walls and ceilings. The paint is durable, resistant to stains, and is easy to sand.
Application	Stir in the water on the surface. Add about 10% additional water if you wish a smoother surface. The surface varies depending on the tool and the thickness of the paint. Brush, or roll with a yarn roller, or spray (high pressure, small nozzle).
Cleaning	Allbäck Linseed Soap. Wash hands and brushes/rollers with Allbäck Linseed Soap and water. Avoid flushing the paint down the drain.
Storage	For short-term storage of the roller, leave it in the paint or in water overnight.
Keeping	Can be stored for at least 4 years at room temperature.
Coverage	10–12 m ² per litre. Paint at least 2 coats. Highly absorbent surfaces can be pre-treated with Allbäck Primer or paint an extra coat.
Dry weight	Approx. 75%
VOC	Less than 0.3%
Drying time	Approximately 24 hours at room temperature with good ventilation. It is possible to paint wet on wet.
Transport	No restrictions – not hazardous goods

Waste management - No specific restrictions.

Let the pigments sink to the bottom. Pour off the water and throw pigment residues in the garbage. Linus left overs can be mixed with chalk or ground pumice and be used as a filler.

The packaging of plastic can be thrown into the ordinary garbage. In Sweden, we have an agreement with REPA on recycling packaging.

Technical Specifications & Safety Data Sheets

These are available on our website www.allbackpaint.com

Cleaning & Maintenance

Once the painted surface has cured after a few weeks, the surface can be washed with Allbäck Linseed Soap and water. Repair painting is possible.

Comments:

The results of applying Allbäck Linus Wall Paint depends on the surface. For highly absorbent surfaces, water damage, soot, or nicotine, pre-treat with Allbäck Primer.

Detailed instructions for use can be found in the Concise Handbook and short video clips on our website. www.allbackpaint.com.

Always test surfaces for approval. In the event of a complaint, present your documentation and quality control.

Treated surface.....
With paint type..... Date.....
I/We have read the instruction manual, carried out the preparatory work and painted.....